

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 5 : H04R 25/00		A1	(11) International Publication Number: WO 91/14351 (43) International Publication Date: 19 September 1991 (19.09.91)
(21) International Application Number: PCT/US91/01760 (22) International Filing Date: 15 March 1991 (15.03.91) (30) Priority data: 495,690 16 March 1990 (16.03.90) US (71)(72) Applicant and Inventor: RAUCH, Robert, A. [US/US]; 21621 Fernleaf, El Toro, CA 92630 (US). (74) Agents: SIMPSON, Andrew, H. et al.; Knobbe, Martens, Olson & Bear, 620 Newport Center Drive, 16th Floor, Newport Beach, CA 92660 (US).		(81) Designated States: AT (European patent), AU, BB, BE (European patent), BF (OAPI patent), BG, BJ (OAPI patent), BR, CA, CF (OAPI patent), CG (OAPI patent), CH (European patent), CM (OAPI patent), DE (European patent), DK (European patent), ES (European patent), FI, FR (European patent), GA (OAPI patent), GB (European patent), GR (European patent), HU, IT (European patent), JP, KP, KR, LK, LU (European patent), MC, MG, ML (OAPI patent), MR (OAPI patent), MW, NL (European patent), NO, RO, SD, SE (European patent), SN (OAPI patent), SU, TD (OAPI patent), TG (OAPI patent). Published <i>With international search report.</i>	
(54) Title: MULTIPURPOSE HEADWEAR			
(57) Abstract Headwear that produces sound from a signal is provided by an audio device in addition to the normal features of the headwear. The audio headwear of the present invention may be configured as a visor, goggles or a headband. In a preferred embodiment, the present invention is an audio visor (20) comprising a flexible body (22), a protective layer (26) and two speaker elements (30, 32). The speaker elements are attached between the flexible body and the protective layer attached to cover the bottom side of the flexible body. Thus, the speaker elements do not interfere with the operation of flexible body as a visor. The preferred embodiment also comprises conductor leads (34) and an amplifier to adapt the output of the audio device for the speaker elements. In the second embodiment, the audio headwear further comprises a lens attached to the flexible body to form goggles or sunglasses.			

BEST AVAILABLE COPY

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	ES	Spain	MG	Madagascar
AU	Australia	FI	Finland	ML	Mali
BB	Barbados	FR	France	MN	Mongolia
BE	Belgium	GA	Gabon	MR	Mauritania
BF	Burkina Faso	GB	United Kingdom	MW	Malawi
BG	Bulgaria	GN	Guinea	NL	Netherlands
BJ	Benin	GR	Greece	NO	Norway
BR	Brazil	HU	Hungary	PL	Poland
CA	Canada	IT	Italy	RO	Romania
CF	Central African Republic	JP	Japan	SD	Sudan
CG	Congo	KP	Democratic People's Republic of Korea	SE	Sweden
CH	Switzerland	KR	Republic of Korea	SN	Senegal
CI	Côte d'Ivoire	LI	Liechtenstein	SU	Soviet Union
CM	Cameroon	LK	Sri Lanka	TD	Chad
CS	Czechoslovakia	LU	Luxembourg	TC	Togo
DE	Germany	MC	Monaco	US	United States of America
DK	Denmark				

MULTIPURPOSE HEADWEAR**Background of the Invention**

The present invention relates generally to wearing
5 apparel and particularly to headwear, such as visors,
headbands or glasses that perform several functions. Still
more particularly, the present invention relates to headwear
that contains earphones or headphones.

Headphones are known for converting electrical signals
10 produced by an AM/FM radio or cassette tape player into
sound waves. Their use has dramatically increased with the
advent of portable AM/FM radios and cassette tape players of
reduced size. Typically, headphones include a pair of
earphones or speaker elements. The earphones are placed
15 directly over the opening of the ear or inserted into the
ear canal of the user. Such placement of the earphones
tends to block other background or warning sounds, such that
they are difficult to hear over the sound produced by the
earphones. This is particularly undesirable for persons
20 engaged in sports activities like skiing, biking or jogging
where conversation or other background sounds can provide
warning of potentially hazardous situations.

The headphones known in the art are also uncomfortable
for many users to wear because of the positioning of the
25 earphones. The earphones can become particularly
uncomfortable when wedged inside the user's ear as required
for proper operation of some earphones. The pressure on
the ears from headphones that cover the ear opening can
also cause discomfort for the user, particularly when used
30 for extended periods of time. If used during sports
activities, the headphones can also be easily dislodged
from the ears, causing the user's attention to be directed
from the sports activity and creating a potentially
hazardous situation.

35 Using headphones while wearing other headwear such as
a hat, visor, headband or glasses can also create other
problems. For example, headphones can be awkward and

unmanageable when used simultaneously with headwear. Removing and putting on headphones and headwear are hampered when the two are used together. Moreover, headwear can interfere with the proper operation of the headphones and vice versa. For example, headwear often
5 fits improperly when used with headphones.

As a result there is a need for headphones that comfortably fit the user and operate properly without interfering with the useful features of headwear.

10 Similarly, even sunglasses can interfere with the proper operation of other headwear such as a hat, visor or headband. The application and removal is especially a problem when sunglasses and other headwear are used together. Thus, a need exists for a device that has both
15 the features of sunglasses and a visor.

Summary of the Invention

The present invention comprises an item of wearing apparel capable of performing several functions. In the preferred embodiments the wearing apparel is capable of
20 producing sound from an electrical signal, and includes a sheet of a first material, a sheet of a second electrically responsive material and a pair of electrical leads. The first material forms wearing apparel and has a surface in proximity to an ear of a user. The second material is
25 mounted in juxtaposition to the first material with at least a portion of the second material free to acoustically vibrate. The leads are connected to the second material and conduct a signal which drives the second material to vibrate so as to produce sound.

30 Preferred embodiments of the present invention are in the form of audio headwear. In the first embodiment, an audio visor comprises a flexible body, a protective layer and two speaker elements that use piezoelectric film. A brim and a pair of straps are integrally formed from the
35 flexible body. The speaker elements are attached on a bottom side of the flexible body. The speaker elements and the bottom side of the flexible body are then covered with

the protective layer for a comfortable fit on the user's head. The speaker elements advantageously utilize piezoelectric film for producing sound because of its light weight, durability and high quality sound reproduction.

5 In a second embodiment, the audio visor includes a lens and a nosepiece to form goggles. The lens is preferably tinted and functions as sunglasses to provide protection from the sun. The second embodiment may also be formed without speaker elements and still operate as a
10 visor and sunglasses.

In the third embodiment, a pair of ear pods are attached to the audio visor. Each ear pod includes an acoustic reflection member and a comfort strip. The ear pods are attached on opposite sides of the visor below the
15 speaker elements to enhance the quality of the sound produced.

In the fourth embodiment, the present invention is configured as a head band. The head band includes a flexible body in the shape of a strip with two enlarged
20 portions to cover the ears of the user and to place the speaker elements near the ears. A protective layer of the same shape is attached on the bottom side of the flexible body to give the head band a comfortable fit.

Brief Description of the Drawings

25 Figure 1 is a perspective view of a first embodiment of the present invention as an audio visor;

Figure 2 is an exploded perspective view of audio visor of Figure 1;

30 Figure 3 is a block diagram of the coupling of the audio visor of Figure 1 to a prior art audio device;

Figure 4A is a schematic diagram of the forward converter portion of the amplifier of the present invention;

35 Figure 4B is a schematic diagram of the amplifier of the present invention;

Figure 5 is a perspective view of a second embodiment of the present invention as goggles;

Figure 6 is a rear elevation view of the goggles of Figure 5;

Figure 7 is an exploded perspective view of the present invention as goggles with an alternate embodiment
5 of the speaker elements;

Figure 8 is a perspective view of a third embodiment of the present invention as an audio visor with ear pods;

Figure 9 is a perspective view of a fourth embodiment of the present invention as a head band;

10 Figure 10 is a bottom perspective view of the goggles of Figure 5 in a flat unused position;

Figure 11 is a cross-sectional view of the goggles taken along line 11-11 of Figure 10; and

15 Figure 12 is a perspective view of the goggles of Figure 10 with the lens folded up when not in use.

Description of the Preferred Embodiments

The present invention comprises wearing apparel that includes earphones for producing sound from an audio device. The earphones are preferably positioned within the
20 wearing apparel and do not interfere with normal use and operation of the wearing apparel. Several preferred embodiments of the wearing apparel illustrating different types of headwear such as a visor, goggles or a headband are described below.

25 Referring to Figure 1, a first embodiment of the present invention as an audio visor 20 is illustrated. The visor 20 is adapted for attachment to the human head and provides shade from the sun. The audio visor 20 comprises a flexible body 22, a fastener 24 and a protective layer 26.
30 The outer surface of the visor 20 is formed by the flexible body 22 on the top and the protective layer 26 on the bottom. As shown in Figure 2, the audio visor 20 further includes two speaker elements 30, 32. Conductor leads 34 are connected to the speaker elements 30, 32, and a
35 connector 36 is connected to the conductor leads 34. The speaker elements 30, 32 and a portion of the leads 34 are mounted between the protective layer 26 and the flexible

body 22, to hide them from view and prevent them from interfering with the wearing of the visor 20.

In the first embodiment, the flexible body 22 is comprised of a flat sheet with a generally parabolic shape, and includes a brim portion 40, as illustrated in Figure 2. A pair of straps or side portions 42, 44 extend from opposite sides of the brim portion 40 to permit mounting of the visor 20 on the user's head. The brim 40 has a generally crescent shape so as to provide a shield to protect the user's face from the sun. The straps 42, 44 are generally rectangular strips and comprise the legs of the parabola formed by the flexible body 22.

As shown in Figure 1, when the visor 20 is in use, the straps 42, 44 and an upper portion 54 of the brim 40 form a generally circular periphery 48 which corresponds to the periphery of the user's head. The straps 42, 44 and the upper portion 54 of the brim 40 are in contact with the user's head, while the remaining portion of the brim 40 extends in a generally horizontal direction which is substantially radially outward from the circular periphery 48.

The flexible body 22 is made of a material sufficiently flexible to allow the straps 42, 44 to be twisted and the brim 40 to be curved for a comfortable fit on the human head. However, the flexible body 22 also has sufficient rigidity for the brim 40 to project in a generally horizontal direction to provide shade from the sun. Preferably, the flexible body 22 is made of wetsuit material approximately 3.0 mm thick. Wetsuit material is advantageous because of its light weight and comfortable fit. In an exemplary embodiment, the flexible body 22 is constructed of neoprene with lycra fabric on the top side. While wetsuit material is preferred, it should be understood that the present invention may be made using other materials.

As mentioned above, the visor 20 includes two speaker elements 30, 32. The speaker elements 30, 32 function as

earphones to convert electrical signals into sound waves. As best illustrated in Figure 2, the speaker elements 30, 32 are made up of layers and have a shape that generally corresponds to the shape of the flexible body 22 in the mounting areas where the brim 40 meets the straps 42, 44. The speaker elements 30, 32 are positioned on the bottom side 46 of the flexible body 22. One speaker element 30, 32 is positioned in each of the two mounting areas so that there is a speaker on each side of the visor 20. The positioning of the speaker elements 30, 32 advantageously provides high quality sound when the visor 20 is worn by the user.

As best illustrated in Figure 2, the protective layer 26 has parabolic shape corresponding to that of the flexible body 22. The protective layer 26 is mounted on a bottom side 46 of the flexible body 22, so that the speaker elements 30, 32 are between the protective layer 26 and body 22. In the first embodiment, the protective layer 26 is mounted to the bottom side 46 of the flexible body 22 using an adhesive, however, other comparable fastening methods such as sewing or bonding may be used. The protective layer 26 is advantageously sized to cover the entire bottom side 46 of the flexible body 22. The layer 26 protects the speaker elements 30, 32 and also hides them from view. The protective layer 26 is preferably made from a comfortable fabric since it is in direct contact with the user's head when visor 20 is worn. The fabric also allows the sound produced by the speaker elements 30, 32 to pass therethrough relatively unchanged to the user's ears.

A fastener 24 is attached on the flexible body 22 and the protective layer 26 to connect the straps 42, 44 and mount the visor 20 on the user's head. The fastener 24 connects the straps 42, 44 together to form the generally circular periphery 48 that fits against the user's head. In the first embodiment, the fastener 24 is preferably a hook and loop fastener. The hook portion 50 of the fastener 24 is attached on the distal end of the protective

layer 26 below the strap 44. The loop portion 52 of the fastener 24 is attached to the top side of the flexible body 22 at the distal end of the other strap 42. The hook portion 50 couples with the loop portion 52 to connect the bottom side of the distal end of the protective layer 26 to the top side of the distal end of the strap 44. Since the distal end of the protective layer 26 is attached on the bottom of the distal end of the strap 42, the fastener 24 effectively connects the bottom side of the strap 42 to the top side of the other strap 44.

The hook 50 and loop 52 portions are advantageously sized to securely fasten the two straps 42, 44 together. The portions 50, 52 have the same size with a width slightly less than that of the straps 42, 44. Preferably, the length of the portions 50, 52 is several inches which advantageously allows for adjustment in the circumference of the circular periphery 48 created when the straps 42, 44 are attached together. Since both portions 50, 52 are several centimeters in length, the amount which the straps 42, 44 overlap can be varied to fit the visor 20 to the size of the user's head while securely fastening the straps 42, 44 together.

Referring to Figure 2, the speaker element 30 will be described with particularity. It should be understood that the speaker elements 30, 32 are identical except that the left speaker 32 is the mirror image of the right speaker 30. Accordingly, only one of the speakers 30, 32 will be described in detail.

In the first embodiment, each speaker element 30, 32 comprises a film 60, a backing sheet 62, and layers of transfer tape 64, 66 and 68. The film 60, the backing sheet 62, and the layers of transfer tape 64, 66 and 68 are all configured with the same outer shape and size so that they may be placed in the speaker mounting areas between the flexible body 22 and the protective layer 26. The film 60 acts like a diaphragm to translate electrical signals into sound waves. In response to the electrical signals applied,

the film 60 deflects in proportion to the voltage applied to produce sound waves. The film 60 is preferably a piezoelectric film. In an exemplary embodiment, the film 60 is a sheet of aluminized Kynar piezo film or high density vinyl fluoride approximately 28 μ M thick that is sized to cover an area of the flexible body 22 approximately 5.0 inches in length where the straps 42, 44 and brim 40 meet. Additionally, it has been discovered that the quality of the sound produced by the film 60 is dramatically improved if a series of holes 78 are made in the film 60. The number of holes 78 and the precise positioning of the holes 78 is not critical, but the film 60 functions optimally when the holes 78 are displaced from the edges of the film 60, such that they are located in an area which acoustically vibrates during operation of the speaker. In an exemplary embodiment, there are three holes 78, approximately .125 inches in diameter, spaced along the center of the film 60. The film 60 is attached to the backing sheet 62 and then both are mounted inside the visor 20.

On the forward end of the film 60 proximate the brim 40 of the visor 20, the film 60 forms a tab 70. The tab 70 provides an area for the leads 34 to be attached to apply the signal to the film 60. One lead 74 is attached on the top of the tab 70 and another lead 76 is attached on the bottom of the tab 70. Conductive connector strips 72 are provided to electrically connect each lead 74, 76 to the film 60. Although only one strip 72 is visible in Figure 2, it will be understood that there is a second strip 72 on the bottom of the tab 70. In the first embodiment, the bottom leads 76 of the left and right speaker elements 30, 32 are preferably coupled together and provide a negative return, while the top leads 74 of the left and right speaker elements 30, 32 provide stereo input channels.

The backing sheet 62 is preferably a layer of stiff plastic that provides rigid support for the film 60. In an exemplary embodiment, the backing sheet 62 is a die cut layer of plastic approximately .01 inches thick that is

also sized for attachment to the flexible body 22. The backing sheet 62 and the film 60 have an identical area and shape.

5 The layers of transfer tape 64, 66 and 68 have adhesive on both sides for attaching the film 60 and the backing sheet 62. The top layer of transfer tape 64 attaches the bottom side 46 of the flexible body 22 to the top side of the backing sheet 62. The top layer 64 is preferably a solid sheet of transfer tape with the same
10 area and shape as the backing sheet 62 to securely fasten the backing sheet 62 to the flexible body 22.

The middle layer 66 of transfer tape is used to attach the bottom side of the backing sheet 62 to the top side of the film 60. However, the middle layer 66 is not a solid
15 sheet like the top layer 64. Since the middle layer 66 only extends about the periphery of the backing sheet 62, the film 60 is only attached to the backing sheet 62 near the peripheral edges of the film 60. Thus, the backing sheet 62 and the middle layer 66 effectively act as a frame
20 and rigidly attach the film 60 about its periphery which allows those portions of the film 60 interior to its peripheral edges to vibrate and produce good quality sound.

Finally, the bottom layer 68 of transfer tape, which is identical in shape to the middle layer 66, attaches the
25 bottom side of the film 60 to the top side of the protective layer 26. The film 60 is attached to the protective layer 26 in the same manner as it is attached to the backing sheet 62 to ensure that the interior of the film 60 is able to vibrate in response to audio signals.

30 The middle and bottom layers 66, 68 are preferably made of electrically conductive transfer tape which conducts the audio signal such that it is applied about the entire periphery of the film 60. Such application of the audio signal improves the audio response of the film 60 and
35 generally enhances the sound quality. In an exemplary embodiment, the middle and bottom layers 66, 68 are die cut layers of conductive 3M® transfer tape. When the layers

66, 68 are attached on the film 60, they contact the connector strips 72 attached to the tab 70 of the film 60.

While the speaker elements 30, 32 have been described as being attached together using layers of transfer tape 5 64, 66 and 68, it should be understood that the speaker elements 30, 32 may be assembled using other types of bonding techniques. Moreover, it should be recognized that the speaker elements 30, 32 may be adapted to any variety of shapes that allow the speaker elements 30, 32 to be 10 positioned in between the flexible body 22 and the protective cover 26.

The audio visor 20 of the present invention also includes an amplifier 38 to produce high quality sound from the signals output by an audio device 80 such as an AM/FM 15 stereo or cassette tape player. As best illustrated by the block diagram in Figure 3, the output of the audio device 80 is coupled through the amplifier 38 to the speaker elements 30, 32 in the audio visor 20. The audio device 80 outputs signals along lead lines 82 to the amplifier 38. 20 The audio device 80 typically outputs signals to provide stereo sound. A right channel signal is provided to drive the right speaker element 30 and a left channel signal for the left speaker element 32. The amplifier 38 modifies the signals received, and outputs signals adapted to drive the 25 speaker elements 30, 32 on lead lines 84. The lead lines 84 are electrically connected to the appropriate speaker element 30, 32 through the connector 36 and the lead lines 34.

The output signals from the audio device 80 are 30 received by the amplifier 38 and modified to a form that will provide enhanced sound quality when the signal is applied to the speaker elements 30, 32. In particular, the amplifier 38 amplifies the signal and performs an impedance matching function. Unlike speakers known in the art, the 35 speaker elements 30, 32 are not inductive but capacitive because of the electrical characteristics of the film 60. Thus, the signal output by the audio device 80, which is

designed for inductive speakers, will not produce high quality sound when coupled directly to the speaker elements 30, 32. The signals output by the audio device 80 must be transformed into a signal that will better deflect the film 5 60 and produce sound.

A circuit diagram for the preferred embodiment of the amplifier 38 is illustrated in Figures 4A and 4B. The amplifier 38 comprises a battery 88, a forward converter 90, two integrators 92, 94, two output stages 96, 97 and 10 other passive components. The battery 88 and forward converter 90 provide the voltage required to amplify the signal provided by the audio device 80. The two integrators 92, 94, and two output stages 96, 97 receive and modify the signals output from the audio device 80. 15 With stereo sound, a different signal is provided for each speaker element 30, 32. Thus, the one integrator 92 and the output stage 96 are used to amplify the right channel signal provided to one speaker element 30 and another integrator 94 and output stage 97 are used to amplify the 20 left channel signal provided to the other speaker element 32.

In a preferred embodiment, the forward converter 90 further includes a standard 555 timer 100, a transformer 102 and an electric switch 104. As illustrated in Figure 25 4A, the battery 88 supplies a voltage of 9.0 DC volts to the forward converter 90. The forward converter 90 transforms the input voltage into an output voltage of approximately 260 DC volts. The battery 88 is coupled across the series connection of the center tap of a primary 30 winding 106 of the transformer 102 and the electric switch 104. In an exemplary embodiment, the electric switch 104 is a MOSFET. The output of the 555 timer 100 is connected to control the opening and closing of the electric switch 104. The 555 timer 100 is coupled with passive components 35 for a stable operation as an oscillator as well known to one skilled in the art. The electric switch 104 is made to open and close because the output of the timer 100

oscillates between high and low, thus, causing alternating current to pass through the primary of the transformer 102. The transformer 102 is used to step up the 9.0 volts applied to the primary winding to 260 volts output by the secondary winding 108. A capacitor 110 is connected in parallel with the secondary winding 108 to remove any AC components, thus, the forward converter 90 provides a 260 DC volt output.

As shown in Figure 4B, the 260 volt potential created by the forward converter 90 is used by two output stages 96, 97 and the two integrators 92, 94 to convert the signals from the audio device 80 into a usable form. Preferably, the integrators 92, 94 are identical and output stages 96, 97 are identical. Thus, only the integrator 92 and the output stage 96 for the right channel will be described for simplicity. As illustrated in Figure 4B, the signal from the audio device 80 is input to the integrator 92. The integrator 92 is formed by an operational amplifier 112, a capacitor 114 and other passive components as known to one skilled in the art. The signal from the audio device 80 is input to through passive components to the positive input of the operational amplifier 112. The output of the integrator 92 is coupled to the input of the output stage 96. The output stage 96 is preferably a Class B output stage formed from four transistors 116-119 as understood by one skilled in the art. In the preferred embodiment, the current source typical in a Class B output stage, is provided by the transistor 119 coupled with other passive components. It should also be noted that the transistors 118, 119 of the output stage are coupled to the output of the forward converter 90, thereby applying a potential of 260 volts to the output stage 96. The signal output by the output stage 96 is then differentiated by the RC differentiator 98 formed by a capacitor 120 and a resistor 122. The output of the differentiator 98 is then coupled to the speaker element 30.

The integrator 92 receives the signal output by the

audio device 80 which has a high voltage output capability for use on inductive speakers. The signal is then integrated by the integrator 92. The output stage 96 then modifies the signal to produce a sizable output current capability or high voltage at low frequency to drive the speaker elements 30, 32. The signal is then differentiated by the RC differentiator 98 to complete the transformation of the signal to one that is equivalent of a current source. Thus, the amplifier 38 basically converts the signal output by the audio device 80 which provides a high voltage output capability for inductive speaker elements to a signal with high current output capability or high voltage at low frequency for capacitive speaker elements.

The present invention will now be discussed with reference to several other embodiments. These other embodiments are often similar to the first embodiment. Thus, where possible, like reference numbers with an "a" suffix have be used to indicate like parts for ease of understanding.

Referring now to Figures 5 and 6, a second preferred embodiment for the audio headwear 130 is illustrated. The second embodiment 130 is similar to the first embodiment and forms a visor comprising a flexible body 22a, a fastener 24a and a protective layer 26a. The embodiment 130 also includes two speaker elements (not shown), a series of leads 34a and a connector 36a to produce sound from electrical signals. The speaker elements are identical to the speaker elements 30, 32 of the first embodiment described above with reference to Figure 2. The second embodiment has the same shape as the first embodiment and is formed by attaching the protective layer 26a and the flexible body 22a together, with the speaker elements therebetween.

The visor of second embodiment additionally provides goggles formed by a wrap-around eye shield having a lens 132, a connecting strip 134 and a nosepiece 136. The lens 132 advantageously shades the user's eyes from sunlight.

Preferably, the lens 132 is a substantially U-shaped sheet of transparent material which is tinted to reduce the intensity of sunlight, and thereby function as sunglasses. For example, the lens 132 may be cut from a sheet of tinted lexan™ or laminated mylar which advantageously makes the lens 132 flexible, light weight and durable. An upper edge 138 of the U-shaped lens 132 is adapted for attachment to the protective layer 26a. A lower edge 140 of the U-shaped lens 132 parallels the upper edge 138. Near the middle of the lens 132, the lower edge 140 extends in toward the upper edge 138 to provide a triangular notch in the lens 132 for receiving the bridge of the user's nose. The nosepiece 136 is attached along the edge 140 of the triangular area. The nosepiece 136 is preferably made from a piece of wetsuit material sized to cover the edge formed by the triangular area. The lens 132 with the nosepiece 136 attached is adapted to rest upon the bridge of the user's nose for a comfortable fit when the second embodiment 130 is worn.

As best seen in Figure 5-7, the lens 132 is attached to the second embodiment 130 using the connecting strip 134. The strip 134 is attached along the upper edge 138 of the lens 132. In a preferred embodiment, the strip 134 extends about .25 inches from the upper edge 138 toward the lower edge 140 and covers a small portion of the lens 132. The remaining portion of the strip 134 not attached to the lens 132 is attached on the bottom side of the protective cover 26a as shown in Figure 6. As best shown in the bottom perspective view of Figure 10, the strip 134 extends along the entire upper edge 138 of the lens 132 from the strap 42a, across the brim 40a, to the other strap 44a. Thus, the strip 134 has a curved or U-shape similar to the lens 132 and forms an arcuate hinge line.

The connecting strip 134 is preferably made of a fabric material which advantageously creates a flexible hinge. While the connecting strip 134 is described as fabric, it should be understood that the strip 134 may be

made of other flexible materials like silicon or polyurethane. As illustrated in the cross sectional view of Figure 11, the hinge is created by the strip 134 which is folded about the upper edge 138 and attached to the exterior side of the lens 132 and the exterior side of the cover 26a. Since the strip 134 is fabric, it may be attached to the cover 26a and the lens 132 by sewing or adhesive. The hinge allows the lower edge 140 of the lens 132 to swing away from the flexible body 22a and the cover 26a as shown by the phantom lines in Figure 11.

The hinge advantageously allows the lens 132 to be configured in several different positions. For example, if the lens 132 is in use, the hinge permits the lens 132 to project away from the cover 26a and form a wrap around eye shield in an open position as illustrated in Figures 5 and 6. The hinge also allows the lens 132 to be contoured to the user's head and lie flat against the cover 26a when the visor is being worn, but the lens 132 is not in use as shown in Figure 12. When neither the visor nor the lens 132 are used, the visor may be collapsed to lie flat with the lens 132 adjacent to the brim 40a, as in Figure 10.

The speaker elements are attached in between the protective layer 26a and the flexible body 22a in the same manner as the first embodiment. The lens 132 advantageously improves the sound quality because the lens 132 extends directly beneath the speakers elements. The lens 132 covers and partially encloses the user's ears in an acoustic chamber formed by (i) the flexible body 22a, (ii) the lens 132 and (iii) the user's head when the second embodiment 130 is worn. The sound produced by the speakers is directed down and reflects off the lens 132. Thus, the lens 132 advantageously amplifies and improves sound quality while allowing background noise to enter the acoustic chamber.

In the second embodiment 130, the speakers 30a, 32a may also take an alternate form. The speaker elements 30a, 32a may be mounted directly on the lens 132 as illustrated

in Figure 7. This increases the sound that is provided to the user's ear since the ends 142 of the lens 132 proximate the straps 42a, 44a cover the ears when the second embodiment 130 is worn. The film 60a that forms the speakers 30a, 32a may be placed in very close proximity to the ears by positioning the film 60a directly on the ends 142 of the lens 132. In this alternate form, the film 60a is advantageously shaped to cover an area proximate the ends 142 of the lens 132. This area extends approximately four inches along the upper 138 and lower 140 edges of the lens 132. Placement of the film 60a upon the lens 132 eliminates the need for a backing sheet and the top layer of transfer tape. However, the alternate form of the speakers 30a, 32a utilizes similar assembly techniques as described above with reference to Figure 2. In particular, a layer of transfer tape (not shown) which forms a strip about the periphery of the film 60a is used to mount the film 60a to the lens 132. The lens 132 and layer of transfer tape cooperate to form a frame for the film 60a in the same manner as the backing sheet 62 and middle layer 66 described above with reference to Figure 2. The alternate form of the speakers 30a, 32a also retains similar electrical connections, as shown in Figure 7, to couple the output of the amplifier 38 to the speakers 30a, 32a. This embodiment for the speaker elements 30a, 32a additionally requires a pair of speaker covers 144, 146. As illustrated in Figure 7, the speaker covers 144, 146 are each placed above a respective layer of film 60a. The speaker covers 144, 146 are attached to the film 60a to protect it and the electrical connections as well as provide a comfortable fit.

While the speaker elements for the second embodiment 130 have been described above in great detail, it should be understood that the goggles of the second embodiment may be constructed without the speaker elements and cover 26a and still form multipurpose headwear. The lens 132 would simply be attached directly to the flexible body 22. Without speaker elements, the second embodiment continues

to operate as both sunglasses and a visor. It should be noted that the exterior appearance and form of the goggles without speakers elements could be the same as the second embodiment disclosed above.

5 Referring now to Figure 8, a third embodiment 150 of the audio visor is illustrated. The third embodiment 150 of the visor has the same basic structure as the first embodiment with the speaker elements (not shown) attached between the flexible body 22a and the protective layer 26a.
10 However, the third embodiment 150 of the audio visor additionally comprises a pair of ear pods 152, 154 for directing the sound produced by the speakers toward the user's ears when the visor is worn.

Each of the ear pods 152, 154 preferably comprises a
15 comfort strip 156, 158 and a reflecting member 160, 162. One comfort strip 156 and reflecting member 160 are located below the right speaker and the other comfort strip 158 and reflecting member 162 are located below the left speaker. Together each comfort strip 156, 158 and its respective
20 reflecting member 160, 162 form an enclosure or ear pod 152, 154 that enhances sound quality while allowing some background noise to be heard.

The reflecting members 160, 162 are shallow cup structures molded from a sheet of plastic, preferably clear
25 lexan™. The reflecting members 160, 162 are tear drop shaped to cover the user's ears. Because of the physical properties of the plastic and its cup shape, the reflecting members 160, 162 advantageously absorb little sound and reflect the sound toward the user's ear. Each reflecting
30 member 160, 162 is attached to its respective side of the visor beneath the speaker elements. The reflecting members 160, 162 extend down from the visor and over the user's ears in substantially vertical direction when the visor is worn.

One comfort strip 156, 158 is attached on the bottom
35 edge of each reflecting member 160, 162. The comfort strips 156, 158 are suitable pieces of material adapted for contact with the human head below the user's ears. The

comfort strips 156, 158 are advantageously made of the wetsuit material like the flexible body 22a. Thus, the user is not irritated if the pods 152, 154 contact the area below the ears. The comfort strips 156, 158 have a substantially rectangular shape that is tapered and narrows near one end. A longitudinal edge of the strips 156, 158 is attached to bottom edge of the reflecting members 160, 162 and the reflecting members 110, 112 extend in towards the user's head when the visor is positioned on the head. In this manner, the comfort strips 156, 158 in combination with the reflecting members create a chamber that enhances the sound quality since the sound is directed down from the bottom of the visor toward the ears.

Finally, referring to Figure 9, a fourth embodiment 170 of the present invention as a headband is illustrated. The headband preferably comprises a flexible body 172, a fastener 24a, a protective layer 26a, and two speaker elements (not shown). A series of leads 34a, and a connector 36a are also included to couple the speaker elements to the audio device 80.

The fourth embodiment 170 is different from previous embodiments primarily because of its shape and function. The flexible body 172, the protective layer 26a and the speaker elements form a strip adapted to be worn about the head and cover the ears. For example, the flexible body 172 is shaped as a slightly curved strip. In an exemplary embodiment, the flexible body 172 is a strip of wetsuit material approximately two inches wide. The flexible body 172 is the same in composition and construction as in other embodiments except that it has a different shape. At two intermediate positions along its length, the flexible body 172 has enlarged portions 174, 176 with a substantially circular shape. The enlarged portions 174, 176 are adapted to cover the ears when the headband 172 is worn. In an exemplary embodiment, the enlarged portions 174, 176 are integrally formed as part of the flexible body 172 and have a diameter of approximately 4.0 inches. Near the center of

each enlarged portion 174, 176, an aperture 178 is provided to permit external sounds to enter the ear.

5 The protective layer 26a is adapted to conform and cover the bottom of the flexible body 172. Thus, the protective layer 26a has the same shape as the flexible body 172 to cover all of bottom side of the flexible body 172. As in previous embodiments, the protective layer 26a is advantageously made of an appropriate fabric for a comfortable fit on the user's head.

10 The speaker elements of the fourth embodiment 170 have a modified shape. In particular, the speaker elements used in the forth embodiment have a generally circular shape adapted for placement of the speaker elements on the enlarged portions 174, 176 respectively. Additionally,
15 rather than the holes 78 used in the film 60 as described above with reference to Figure 2, the fourth embodiment 170 has a single hole in the film of the speaker elements corresponding in position to the aperture 178 in the enlarged portions 174, 176 of the flexible body 172.
20 However, the speaker elements have the same layered construction as described with reference to Figure 2 above with the only distinction being the shape of the elements.

Having described the invention in connection with certain preferred embodiments thereof, it will be
25 understood that many modifications and variations thereto are possible, all of which fall within the true spirit and scope of this invention. In particular, the present invention has been discussed primarily as headwear, but it should be understood that the present invention may be
30 adapted for many different types of wearing apparel. For example, the present invention may be utilized in a jacket with a collar having film and leads attached therein to produce sound.

WHAT IS CLAIMED IS:

1. An apparatus, comprising:
an item of wearing apparel comprising a sheet of
a first material having a surface in proximity to an
ear of a user;
a sheet of a second electrically responsive
material mounted in juxtaposition to said sheet of
first material such that at least a portion of said
second electrically responsive material is free to
acoustically vibrate; and
an electrical lead connected to said second
material for conducting a signal which drives said
second material to vibrate in accordance with said
signal to produce sound.
2. The apparatus of Claim 1, wherein said item of
wearing apparel comprises headwear.
3. The apparatus of Claim 2, wherein said headwear
comprises a visor.
4. The apparatus of Claim 3, wherein said visor
comprises a brim portion and a pair of side portions.
5. The apparatus of Claim 4, wherein said visor is
comprised of neoprene.
6. The apparatus of Claim 3, wherein said headwear
additionally comprises an eye shield attached to said
visor, said eye shield being comprised of transparent
material.
7. The apparatus of Claim 6, wherein said eye shield
is attached to said brim portion and said side portions,
such that said eye shield covers the user's eyes and wraps
around the sides of the user's head to form goggles.
8. The apparatus of Claim 7, wherein said eye shield
is mechanically hinged to said visor such that said eye
shield has a first position in which said transparent
material lies flat against said brim and a second position
in which said transparent material is bent to form said
goggles.

9. The apparatus of claim 8, wherein said goggles are frameless.

10. The apparatus of Claim 9, wherein said goggles at least partially extend over the ears of the user.

5 11. The apparatus of Claim 1, wherein said second material comprises a piezoelectric film.

12. The apparatus of Claim 11, wherein said film is rigidly mounted on said sheet of first material only along peripheral edges of said film to allow portions of said
10 film interior to said edges to vibrationally move.

13. The apparatus of Claim 12, wherein said sheet of first material comprises neoprene.

14. The apparatus of Claim 1, wherein said item of wearing apparel comprises a headband.

15 15. The apparatus of Claim 3, wherein said surface in proximity to an ear of a user comprises a surface of said visor, and wherein said sheet of second material comprises a piezoelectric film mounted on the surface of the visor.

16. The apparatus of Claim 1, wherein said sheet of
20 second material has at least one aperture therethrough.

17. The apparatus of Claim 11, additionally comprising a conductor which distributes said signal along a periphery of said film.

18. An apparatus comprising:

25 a flexible body adapted for mounting on the head, said flexible body forming a piece of headwear;

an eye shield attached to said flexible body, said eye shield being comprised of transparent material;

30 a sheet of a second electrically responsive material mounted in juxtaposition to said eye shield such that at least a portion of said second electrically responsive material is free to acoustically vibrate; and

35 a pair of electrical leads connected to said second material for conducting a signal which drives said second material to vibrate in accordance with

said signal to produce sound.

19. The apparatus of Claim 18 wherein said flexible body comprises neoprene.

20. The apparatus of Claim 18 wherein said eye shield
5 is transparent plastic.

21. An apparatus worn on the head for producing sound from an audio device, said apparatus comprising:

a flexible body adapted for mounting on the head,
said flexible body forming a piece of headwear;

10 a piezoelectric speaker element attached to said flexible body; and

means for coupling said speaker element to the audio device;

22. The apparatus of Claim 21, further comprising:

15 a protective layer sized to cover a bottom side of said flexible body, said protective layer attached over the bottom side of said flexible body and said speaker element; and

20 wherein said piezoelectric speaker element is sized for placement between said flexible body and said protective layer.

23. The apparatus of Claim 22, wherein said protective layer is fabric suitable for contact with the head.

25 24. The apparatus of Claim 21, further comprising:

a second piezoelectric speaker element attached to said flexible body, said second piezoelectric speaker element coupled to produce sound from a right channel signal; and

30 wherein said piezoelectric speaker element is coupled to produce sound from a left channel signal, said piezoelectric speaker element and second piezoelectric speaker element thereby producing stereo sound.

35 25. The apparatus of Claim 21, wherein said piezoelectric speaker element has a layered construction including a sheet of piezoelectric film, a plurality of

layers of conductive transfer tape and a backing sheet.

26. The apparatus of Claim 21, further comprising a fastener attached to said flexible body, said fastener providing adjustability for mounting the apparatus on heads
5 of different size.

27. The apparatus of Claim 26, wherein said fastener is a hook and loop fastener, with a hook portion and a loop portion attached on opposite ends of the flexible body.

28. The apparatus of Claim 21, wherein said coupling
10 means comprises conductor leads and an electrical connector.

29. The apparatus of Claim 28, wherein said coupling means further comprises an amplifier to convert the signal output by the audio device for application to said
15 piezoelectric speaker element, the input to said amplifier coupled to the output of said audio device and the output from said amplifier coupled to said connector.

30. The apparatus of Claim 21, wherein said flexible body is substantially parabolic in shape and forms a visor.

20 31. The apparatus of Claim 30, wherein said flexible body is a sheet of wetsuit material approximately 3.0 mm thick.

32. The apparatus of Claim 21, further comprising:
a lens adapted to improve the sound produced by
25 said speaker element and partially block out sunlight, said lens attached to said flexible body; and
a nosepiece attached along an edge of said lens, said nosepiece shaped to conform to the bridge of the nose for a comfortable fit.

30 33. The apparatus of Claim 32, wherein said flexible body has a substantially parabolic shape, said flexible body with said lens attached thereon forming sunglasses.

34. The apparatus of Claim 33, wherein said lens has a generally U-shape.

35 35. The apparatus of Claim 34, wherein said lens is made from a curved strip of tinted Lexan™.

36. The apparatus of Claim 35, wherein said nosepiece

is a V-shaped strip of wetsuit material.

37. The apparatus of Claim 23, further comprising a pair of ear pods, said ear pods attached and extending beneath said flexible body, said ear pods enhancing the sound produced by said speaker element.

38. The apparatus of Claim 37, wherein each said ear pod comprises a reflecting member and a comfort strip, an upper edge of said reflecting member connected beneath the flexible body and a lower edge of said reflecting member connected to the comfort strip, said comfort strip and reflecting member forming an enclosure to direct the sound produced by said speaker element to the ears.

39. The apparatus of Claim 38, wherein said reflecting members are a cupped sheet portion of Lexan[™] and said comfort strips are wetsuit material.

40. The apparatus of Claim 21, wherein said flexible body is a curved strip forming a headband, said flexible body having enlarged portions intermediate the distal ends of said flexible body, said enlarged portions adapted to cover the ears.

41. The apparatus of Claim 40, wherein said flexible body is strip about 2 inches wide and said enlarged portions have a substantially circular shape about 4 inches in diameter.

42. An audio visor for producing sound from an audio device comprising:

a flexible body adapted for mounting on the head, said flexible body forming visor;

a first and second speaker elements attached on a bottom side of said flexible body, said speaker elements formed from a sheet of piezoelectric film;

a protective layer sized to cover the bottom side of said flexible body, said protective layer attached over the bottom side of said flexible body and said speaker elements;

means for coupling said speaker elements to the audio device;

a fastener adapted to adjust the flexible body for mounting on heads of different size, said fastener connecting ends of said flexible body; and

5 a generally U-shaped lens for protecting the eyes from sunlight and improving the sound produced by said speaker elements, said lens attached to said flexible body.

43. A method of manufacturing an audio device, comprising:

10 providing an item of wearing apparel having a surface which is in proximity to at least one ear of a user when said apparel is worn by said user; and

15 mounting a sheet of electrically responsive material on said surface such that a portion of said sheet is free to acoustically vibrate when driven by electrical signals.

44. The method of Claim 43, wherein said mounting step comprises affixing said sheet to said surface at peripheral edges of said sheet such that portions of said 20 sheet interior to said peripheral edges are free to acoustically vibrate.

45. The method of Claim 43 additionally comprising the step of forming at least one aperture in said sheet.

25 46. The method of Claim 45, wherein said aperture is spaced by a significant distance from said peripheral edges, such that said aperture is in a central area of said sheet.

47. An apparatus forming an item of wearing apparel, comprising:

30 a visor, formed from a sheet of a first material, having first and second side portions and a brim portion therebetween;

an eye shield, formed from a sheet of a second material; and

35 a flexible hinge for connecting said eye shield to said visor along an arcuate hinge line which extends from said first side portion through said brim

portion to said second side portion, said hinge mounting said eye shield such that said eye shield has first and second positions, said first position orienting said eye shield to project from said brim so as to shield the eyes of a user, said second position orienting said eye shield against a surface of said visor to store said shield when not shielding the user's eyes.

48. The apparatus of Claim 47, wherein said eye shield comprises tinting to reduce the light intensity reaching the user's eyes.

49. The apparatus of Claim 47, wherein said visor is formed of a generally crescent shaped sheet of said first material and said eye shield is formed of a generally crescent shaped sheet of said second material.

50. The apparatus of Claim 47, wherein said second material is lexan[™] or mylar.

51. The apparatus of Claim 47, wherein said first material is wetsuit material.

52. The apparatus of Claim 47, wherein said eye shield is connected to said hinge along an arcuate edge of said eye shield, said arcuate edge being coextensive with said arcuate hinge line.

53. The apparatus of Claim 47, wherein said hinge is formed by fabric attached to said visor and said eye shield.

1/9




Fig. 1




Fig. 2




Fig. 3




Fig. 4A




Fig. 4B

5/9




Fig. 5





Fig. 6

*Fig. 7*

7/9




Fig. 8




Fig. 9

8/9

Fig. 10





Fig. 11




Fig. 12

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US91/01760

I. CLASSIFICATION OF SUBJECT MATTER (if several classification symbols apply, indicate all) *

According to International Patent Classification (IPC) or to both National Classification and IPC

IPC(5) : H04R 25/00

US CL : 381/25, 24, 183, 187

II. FIELDS SEARCHED

Minimum Documentation Searched *

Classification System

Classification Symbols

US

381/25, 24, 183, 187

Documentation Searched other than Minimum Documentation
to the extent that such Documents are included in the Fields Searched *

III. DOCUMENTS CONSIDERED TO BE RELEVANT **

Category *	Citation of Document, ** with indication, where appropriate, of the relevant passages **	Relevant to Claim No. **
X Y	US, A, 4,856,089 (HORTON) 08 AUGUST 1989 See abstract and the entire document.	1-10, 14, 16, 18-20, 43-46, 47-49, 52-53 11-13, 15, 17, 21-42 and 50-51
Y	US, A, 4,638,207 (RADICE) 20 JANUARY 1987 See figs. 1-7 and the abstract.	11-13, 15, 17, 21-42, 50-51
A	US, A, 4,864,619 (SPATES) 05 SEPTEMBER 1989 See figs 1-3.	
A	US, A, 4,565,258 (BUTLER ET AL.) 21 JANUARY 1986 See abstract.	
A	US, A, 4,682,363 (GOLDFARB ET AL) 21 JULY 1987 See entire document.	
A	US, A, 3,696,357 (KILGORE) 03 OCTOBER 1972 See abstract.	
A	US, A, 4,727,599 (RAPAPORT ET AL) 23 FEBRUARY 1988 See figs 1-3.	

* Special categories of cited documents: **

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

IV. CERTIFICATION

Date of the Actual Completion of the International Search *

Date of Mailing of this International Search Report *

02 MAY 1991

13 JUN 1991

International Searching Authority *

ISA/US

Signature of Authorized Officer **
MICHAEL RAZAVI
INTERNATIONAL DIVISION
MICHAEL RAZAVI